

**2020**  
—

**LED Downlight**

**CATALOG**





## Nona Series

### Detail

Nona LED Downlight  
 Watt: 5W, 7W, 10W, 15W, 20W, 30W  
 Input voltage: AC220-240V 50/60Hz  
 LED Brand: CREE COB, CITIZEN COB  
 CCT: 2700K-6000K for optional  
 Ra: >80 (>90 for optional)  
 Beam angle: 10°, 15°, 24°, 36°, 38°, 60°  
 Light efficiency: 75-80LM/W, 90-95LM/W  
 Driver: Eaglerise, Lifud, BOKE, OSRAM, PHILIPS, TRIDONIC  
 Dimming: non-dim, phase dim, 1-10V dim, Dali dim for optional  
 Finish: White (other colour on request), Powder coating

Model No.	Watt	Dimension
NONA-5W	5W	cut-out: $\Phi$ 55mm
NONA-7W	7W	cut-out: $\Phi$ 55mm
NONA-10W	10W	cut-out: $\Phi$ 75mm
NONA-15W	15W	cut-out: $\Phi$ 95mm
NONA-20W	20W	cut-out: $\Phi$ 125mm
NONA-30W	30W	cut-out: $\Phi$ 125mm

## Bono Series



### Detail

Bono LED Downlight  
 Watt: 5W, 10W, 15W, 20W, 30W  
 Input voltage: AC220-240V 50/60Hz  
 LED Brand: CREE COB, CITIZEN COB  
 CCT: 2700K-6000K for optional  
 Ra: >80 (>90 for optional)  
 Beam angle: 24°, 40°, 60°  
 Light efficiency: 75-80LM/W, 90-95LM/W  
 Driver: Eaglerise, OSRAM-Element, EUCHIPS, TRIDONIC driver  
 Dimming: non-dim, phase dim, 1-10V dim, Dali dim for optional

Model No.	Watt	Dimension
Bono-5W	5W	cut-out: $\Phi$ 75mm
Bono-10W	10W	cut-out: $\Phi$ 95mm
Bono-15W	15W	cut-out: $\Phi$ 95mm
Bono-20W	20W	cut-out: $\Phi$ 120mm
Bono-30W	30W	cut-out: $\Phi$ 140mm



### Mano Series

#### Detail

Mano LED Downlight

Watt: 5W, 7W, 10W, 15W, 20W, 30W, 40W, 50W, 60W

Input voltage: AC220-240V 50/60Hz

LED Brand: CREE COB, CITIZEN COB

CCT: 2700K-6000K for optional

Ra: >80 (>90 for optional)

Beam angle: 24°, 40°, 60°

Light efficiency: 75-80LM/W, 90-95LM/W

Driver: Eaglerise, OSRAM-Element, EUCHIPS, TRIDONIC driver

Dimming: non-dim, phase dim, 1-10V dim, Dali dim for optional

Model No.	Watt	Dimension
Mano-5W	5W	cut-out: $\Phi$ 75mm
Mano-10W	10W	cut-out: $\Phi$ 95mm
Mano-15W	15W	cut-out: $\Phi$ 95mm
Mano-20W	20W	cut-out: $\Phi$ 130mm
Mano-30W	30W	cut-out: $\Phi$ 140mm
Mano-40W	40W	cut-out: $\Phi$ 140mm
Mano-50W	50W	cut-out: $\Phi$ 140mm

### Jaga Series



#### Detail

Jaga LED Downlight

Watt: 10W, 18W, 30W, 40W, 50W

Input voltage: AC220-240V 50/60Hz

LED Brand: CREE COB, CITIZEN COB

CCT: 2700K-6000K for optional

Ra: >80 (>90 for optional)

Beam angle: 24°, 38°, 55° (10W only 50°)

Light efficiency: 75-80LM/W, 90-95LM/W

Driver: Eaglerise, OSRAM-Element, EUCHIPS, TRIDONIC driver

Dimming: non-dim, phase dim, 1-10V dim, Dali dim for optional

Model No.	Watt	Dimension
Jaga-10W	10W	cut-out: $\Phi$ 70mm
Jaga-15W	15W	cut-out: $\Phi$ 85mm
Jaga-20W	20W	cut-out: $\Phi$ 120mm
Jaga-30W	30W	cut-out: $\Phi$ 160mm
Jaga-40W	40W	cut-out: $\Phi$ 195mm



### Godan Series Round

#### Detail

Godan LED Downlight-Round  
 Watt: 10W, 20W, 30W, 40W, 50W  
 Input voltage: AC220-240V 50/60Hz  
 LED Brand: CREE COB, CITIZEN COB  
 CCT: 2700K-6000K for optional  
 Ra: >80 (>90 for optional)  
 Beam angle: 50°  
 Light efficiency: 75-80LM/W, 90-95LM/W  
 Driver: Eaglerise,OSRAM-Element,EUCHIPS,TRIDONIC driver  
 Dimming: non-dim, phase dim, 1-10V dim, Dali dim for optional

Model No.	Watt	Dimension
GodanR-10W	10W	cut-out: Φ100mm
GodanR-20W	20W	cut-out: Φ125mm
GodanR-30W	30W	cut-out: Φ145mm
GodanR-40W	40W	cut-out: Φ180mm
GodanR-50W	50W	cut-out: Φ215mm

### Godan Series Square



#### Detail

Godan LED Downlight-Square  
 Watt: 10W, 20W, 30W, 40W, 50W  
 Input voltage: AC220-240V 50/60Hz  
 LED Brand: CREE COB, CITIZEN COB  
 CCT: 2700K-6000K for optional  
 Ra: >80 (>90 for optional)  
 Beam angle: 50°  
 Light efficiency: 75-80LM/W, 90-95LM/W  
 Driver: Eaglerise,OSRAM-Element,EUCHIPS,TRIDONIC driver  
 Dimming: non-dim, phase dim, 1-10V dim, Dali dim for optional

Model No.	Watt	Dimension
GodanS-10W	10W	cut-out: L100mm
GodanS-20W	20W	cut-out: L125mm
GodanR-30W	30W	cut-out: L145mm
GodanS-40W	40W	cut-out: L180mm
GodanS-50W	50W	cut-out: L215mm



### WaWa Series

#### Detail

WaWa LED Downlight  
 Watt: 10W, 20W, 30W  
 Input voltage: AC220-240V 50/60Hz  
 LED Brand: CREE COB, CITIZEN COB  
 CCT: 2700K-6000K for optional  
 Ra: >80 (>90 for optional)  
 Beam angle: Polarized 10°  
 Light efficiency: 75-80LM/W, 90-95LM/W  
 Driver: Eaglerise, OSRAM-Element, EUCHIPS, TRIDONIC driver  
 Dimming: non-dim, phase dim, 1-10V dim, Dali dim for optional

Model No.	Watt	Dimension
WaWa-10W	10W	cut-out: Φ75mm
WaWa-20W	20W	cut-out: Φ95mm
WaWa-30W	30W	cut-out: Φ125mm

### Swim Series



#### Detail

Swim LED Downlight-Waterproof IP67  
 Watt: 10W, 20W, 30W, 40W  
 Input voltage: AC220-240V 50/60Hz  
 LED Brand: CREE COB, CITIZEN COB  
 CCT: 2700K-6000K for optional  
 Ra: >80 (>90 for optional)  
 Beam angle: 45° (40W: 30°)  
 Light efficiency: 75-80LM/W, 90-95LM/W  
 Driver: Waterproof driver  
 Dimming: non-dim, phase dim, 1-10V dim, Dali dim for optional  
 Finish: White (other colour on request), Powder coating

Model No.	Watt	Dimension
Swim-10W	10W	cut-out: Φ90mm
Swim-20W	20W	cut-out: Φ130mm
Swim-30W	30W	cut-out: Φ170mm
Swim-40W	40W	cut-out: Φ200mm



## Fany Series

### Detail

Fany LED Downlight  
 Watt: 15W, 20W, 30W, 40W  
 Input voltage: AC220-240V 50/60Hz  
 LED Brand: PHILIPS 2835SMD  
 CCT: 2700K-6000K for optional  
 Ra: >80 (>90 for optional)  
 Beam angle: 90°  
 Light efficiency: 100LM/W  
 Driver: Lifud, BOKE, PHILIPS, TRIDONIC  
 Dimming: non-dim, phase dim, 1-10V dim, Dali dim for optional  
 Finish: White (other colour on request), Powder coating

Model No.	Watt	Dimension
Fany-15W	15W	cut-out: Φ95mm
Fany-20W	20W	cut-out: Φ130mm
Fany-30W	30W	cut-out: Φ170mm
Fany-40W	40W	cut-out: Φ210mm

## Pino Series



### Detail

Pino LED Downlight  
 Watt: 10W, 20W, 30W  
 Input voltage: AC220-240V 50/60Hz  
 LED Brand: PHILIPS 2835SMD  
 CCT: 2700K-6000K for optional  
 Ra: >80 (>90 for optional)  
 Beam angle: 90°  
 Light efficiency: 100LM/W  
 Driver: Lifud, BOKE, PHILIPS, TRIDONIC  
 Dimming: non-dim, phase dim, 1-10V dim, Dali dim for optional  
 Finish: White (other colour on request), Powder coating

Model No.	Watt	Dimension
Pino-10W	10W	cut-out: Φ125mm
Pino-20W	20W	cut-out: Φ160mm
Pino-30W	30W	cut-out: Φ200mm





### Sany Series

#### Detail

Sany LED Downlight  
 Watt: 15W, 20W, 30W  
 Input voltage: AC220-240V 50/60Hz  
 LED Brand: PHILIPS 2835SMD  
 CCT: 2700K-6000K for optional  
 Ra: >80 (>90 for optional)  
 Beam angle: 90°  
 Light efficiency: 100LM/W  
 Driver: Lifud, BOKE, PHILIPS, TRIDONIC  
 Dimming: non-dim, phase dim, 1-10V dim, Dali dim for optional  
 Finish: White (other colour on request), Powder coating

Model No.	Watt	Dimension
Sany-15W	15W	cut-out: $\Phi$ 125mm
Sany-20W	20W	cut-out: $\Phi$ 160mm
Sany-30W	30W	cut-out: $\Phi$ 210mm

### Qino Series



#### Detail

Qino LED Downlight  
 Watt: 40W, 80W  
 Input voltage: AC220-240V 50/60Hz  
 LED Brand: CITIZEN COB  
 CCT: 2700K-6000K for optional  
 Ra: >80 (>90 for optional)  
 Beam angle: 24°, 38°, 45°, 60°  
 Light efficiency: 100LM/W  
 Driver: Lifud, BOKE, PHILIPS, TRIDONIC  
 Dimming: non-dim, phase dim, 1-10V dim, Dali dim for optional  
 Finish: White (other colour on request), Powder coating

Model No.	Watt	Dimension
Qino-40W	40W	cut-out: $\Phi$ 150mm
Qino-80W	80W	cut-out: $\Phi$ 200mm



## Snow Series

### Detail

Snow Gimbal LED Downlight

Watt: 20W, 30W, 40W

Input voltage: AC220-240V 50/60Hz

LED Brand: CREE COB, CITIZEN COB

CCT: 2700K-6000K for optional

Ra: >80 (>90 for optional)

Beam angle: 15°, 24°, 38°, 60°

Light efficiency: 75-80LM/W, 90-95LM/W

Driver: Lifud, BOKE, PHILIPS, TRIDONIC

Dimming: non-dim, phase dim, 1-10V dim, Dali dim for optional

Finish: White (other colour on request), Powder coating

Model No.	Watt	Dimension
Snow-20W	20W	cut-out: $\Phi$ 125mm
Snow-30W	30W	cut-out: $\Phi$ 145mm
Snow-40W	40W	cut-out: $\Phi$ 170mm

## Jana Series



### Detail

Jana LED Downlight

Watt: 30W, 60W

Input voltage: AC220-240V 50/60Hz

LED Brand: CREE COB, CITIZEN COB

CCT: 2700K-6000K for optional

Ra: >80 (>90 for optional)

Beam angle: 15°, 24°, 36°, 60°

Light efficiency: 75-80LM/W, 90-95LM/W

Driver: Lifud, BOKE, PHILIPS, TRIDONIC

Dimming: non-dim, phase dim, 1-10V dim, Dali dim for optional

Finish: White (other colour on request), Powder coating

Model No.	Watt	Dimension
Jana-30W	30W	cut-out: $\Phi$ 150mm
Jana-30W	30W	cut-out: L150mm
Jana-60W	60W	cut-out: L320*W160mm





## Grille Series

### Detail

#### Grille LED Downlight

Watt: 7W, 15W, 20W, 30W; 2\*7W, 2\*15W, 2\*20W, 2\*30W;  
3\*7W, 3\*15W, 3\*20W, 3\*30W

Input voltage: AC220-240V 50/60Hz

LED Brand: CREE COB, CITIZEN COB

CCT: 2700K-6000K for optional

Ra: >80 (>90 for optional)

Beam angle: 10°, 24°, 38°, 60°

Light efficiency: 75-80LM/W, 90-95LM/W

Driver: Lifud, BOKE, PHILIPS, TRIDONIC

Dimming: non-dim, phase dim, 1-10V dim, Dali dim for optional

Model No.	Watt	Dimension
Grille-7W	7W	cut-out: L100*W100
Grille-15W	15W	cut-out: L125*W125
Grille-20W	20W	cut-out: L145*W145
Grille-30W	30W	cut-out: L165*W165
Grille-2*7W	7W	cut-out: L200*W100
Grille-2*15W	15W	cut-out: L250*W125
Grille-2*20W	20W	cut-out: L290*W145
Grille-2*30W	30W	cut-out: L330*W165
Grille-3*7W	7W	cut-out: L300*W100
Grille-3*15W	15W	cut-out: L375*W125

Model No.	Watt	Dimension
Grille-3*20W	20W	cut-out: L440*W145
Grille-3*30W	30W	cut-out: L500*W165



## Salo Series

### Detail

Salo Surface Mounted Downlight  
 Watt: 9W, 15W, 25W, 35W, 45W  
 Input voltage: AC220-240V 50/60Hz  
 LED Brand: CREE COB, CITIZEN COB  
 CCT: 2700K-6000K for optional  
 Ra: >80 (>90 for optional)  
 Beam angle: 20°, 45°  
 Light efficiency: 75-80LM/W, 90-95LM/W  
 Driver: Eaglerise, OSRAM-Element, EUCHIPS, TRIDONIC driver  
 Dimming: non-dim, phase dim, 1-10V dim, Dali dim for optional

Model No.	Watt	Dimension
SaloR-9W	9W	Φ90*H90mm
SaloR-15W	15W	Φ110*H120mm
SaloR-25W	25W	Φ130*H152mm
SaloR-35W	35W	Φ170*H185mm
SaloR-45W	45W	Φ193*H193mm

## Salo Square



### Detail

Salo Surface Mounted Downlight Square  
 Watt: 10W, 20W, 30W, 40W  
 Input voltage: AC220-240V 50/60Hz  
 LED Brand: CREE COB, CITIZEN COB  
 CCT: 2700K-6000K for optional  
 Ra: >80 (>90 for optional)  
 Beam angle: 20°, 45°  
 Light efficiency: 75-80LM/W, 90-95LM/W  
 Driver: Eaglerise, OSRAM-Element, EUCHIPS, TRIDONIC driver  
 Dimming: non-dim, phase dim, 1-10V dim, Dali dim for optional

Model No.	Watt	Dimension
SaloS-10W	10W	L90*H90mm
SaloS-20W	20W	L110*H120mm
SaloS-30W	30W	L130*H135mm
SaloS-40W	40W	L160*H165mm



### Baso Series Round

#### Detail

Baso Surface Mounted Downlight Round  
 Watt: 9W, 15W, 25W, 35W, 45W  
 Input voltage: AC220-240V 50/60Hz  
 LED Brand: CREE COB, CITIZEN COB  
 CCT: 2700K-6000K for optional  
 Ra: >80 (>90 for optional)  
 Beam angle: 50°  
 Light efficiency: 75-80LM/W, 90-95LM/W  
 Driver: Eaglerise,OSRAM-Element,EUCHIPS,TRIDONIC driver  
 Dimming: non-dim, phase dim, 1-10V dim, Dali dim for optional

Model No.	Watt	Dimension
BasoR-9W	9W	Φ90*H90mm
BasoR-15W	15W	Φ110*H120mm
BasoR-25W	25W	Φ130*H152mm
BasoR-35W	35W	Φ170*H185mm
BasoR-45W	45W	Φ193*H193mm

### Baso Series Square



#### Detail

Baso Surface Mounted Downlight Square  
 Watt: 10W, 20W, 30W, 40W  
 Input voltage: AC220-240V 50/60Hz  
 LED Brand: CREE COB, CITIZEN COB  
 CCT: 2700K-6000K for optional  
 Ra: >80 (>90 for optional)  
 Beam angle: 50°  
 Light efficiency: 75-80LM/W, 90-95LM/W  
 Driver: Eaglerise,OSRAM-Element,EUCHIPS,TRIDONIC driver  
 Dimming: non-dim, phase dim, 1-10V dim, Dali dim for optional

Model No.	Watt	Dimension
BasoS-10W	10W	L90*H90mm
BasoS-20W	20W	L110*H120mm
BasoS-30W	30W	L130*H135mm
BasoS-40W	40W	L160*H165mm



## Waso Series

### Detail

Waso Surface Mounted Downlight

Watt: 10W, 15W, 20W, 30W, 40W, 50W, 60W

Input voltage: AC220-240V 50/60Hz

LED Brand: CREE COB, CITIZEN COB

CCT: 2700K-6000K for optional

Ra: >80 (>90 for optional)

Beam angle: 20°, 40°

Light efficiency: 75-80LM/W, 90-95LM/W

Driver: waterproof driver

Dimming: non-dim, phase dim, 1-10V dim, Dali dim for optional

Finish: White (other colour on request), Powder coating

Model No.	Watt	Dimension
Waso-10W	10W	Φ75*H100mm
Waso-15W-2	15W	Φ95*H100mm
Waso-20W	20W	Φ95*H152mm
Waso-30W	30W	Φ115*H152mm
Waso-40W	40W	Φ140*H162mm
Waso-50W	50W	Φ170*H182mm
Waso-60W	60W	Φ205*H212mm